

# MBS ACCESS

01376 583 967

WWW.MBSACCESS.CO.UK

CMC S15



Non Marking Rubber Tracks

Narrow tracked boom lift

It is ultra-compact

The S15 can pass through a single doorway and manoeuvre in the tightest of spaces

The shortest length and closed height of any machine in this class, with a 2.7m stabiliser base width

Simple controls system, fault code diagnosis, easy to repair on site

Articulating boom, with telescopic and jib

Innovative basket design

Impressive height and outreach performance

Low weight & compact suitable for towing

NOW AVAILABLE IN  
LITHIUM



MEASUREMENTS	METRIC (M)
Working Height	15m
Horizontal Outreach	7m
Safe Load in Cage	200kg
Cage Rotation	356°
Cage Dimensions	1400x700x1100mm
Length With Cage	4148mm
Width With Cage	1270mm
Length Without Cage	3420mm
Width Without Cage	780mm
Machine Height	1897mm
Overall Weight	1955kg
Jacked up on ground slope of & Gradeability	30%
Engine	Kubota 110/230v
SET UP POSITIONS	
<b>Standard</b>	
Length	3100mm
Width	3100mm
Set Up Ability	12%
Point Load On 400x400 Pads	7.5 N/CM2
Adjustable Track Height/Width	780mm-1170mm

