

MBS ACCESS

01376 583 967

WWW.MBSACCESS.CO.UK

FALCON FS330Z



Automatic stability & outreach control

Computer controlled (can-bus)

Proportional control of all functions

Self-propelled 2 speed selection

Battery powered with charger 180 Ah

Jib-arm 110°

375° turret rotation, with integrated stop

+/- 90° basket rotation

Minimum width only 1, 10 m

Electronic checking of the power system (PLC)

Individual setting of each outrigger

Non-marking Tracks

110v/220V AC power supply in the basket

Wireless remote control of all functions

Storage room in chassis with lock

Space for tools etc. in basket

Manual pump system for emergency lowering

Ability to self-load onto trucks or trailers



MEASUREMENTS	METRIC (M)
Working Height	33m
Horizontal Outreach 100kg	19m
Horizontal Outreach 200kg	16m
Jib Arm	110 °
Basket Capacity	200kg
Basket Rotation	+/-90
Turret Rotation	375 °
Weight with Standard Equipment	5900kg
Surface Pressure - Soft Surface	0.85kg/cm ²
Surface Pressure – Hard Surface	3kg/cm ²
Max Ground Pressure Under 1 Outrigger Pad	3.40kg/cm ²
Max Slope Gradeability	20 °
Slope Gradeability Horizontal	7.5 °
SET UP POSITIONS	
Narrow	1100mm
Wide	1500mm
DIMENSIONS TRANSPORT POSITION	
Height	2.27m
Length	7.4m
Width	1.1-1.5m
Gradeability	20/37%
Weight Approx.	5.900kg

