

MBS ACCESS

01376 583 967

WWW.MBSACCESS.CO.UK

MULTITEL SMX 250



This tracked spider has a max working height of 25.2m

Outreach of 11.65m

Narrow and standard jacking

Diesel and electric motors for working outside and in

It has good basket rotation, and a 360° slew

The unit is light enough to be towed by a standard 4x4

All in all, a very versatile platform

Automatic outrigger levelling

Max surmountable slope of 11°

Non marking tracks

Lightest 25m machine available - only 2,660kg - ideal for craning

Good ground clearance for rough terrain



MEASUREMENTS	METRIC (M)
Working Height	25.20m
Horizontal Outreach 80g	11m
Horizontal Outreach 200g	8m
Platform Height	23.20m
Fully Extended Stabilizers	8.55m
Partially Extended Stabilizers	7m
Turret Rotation	360°
Cage Rotation	90°+90°
Boom Telescopic Amplitude	5.25+6.40
Max Cage Dimensions	1.40x0.70x1.10m
Safe Working Load on Cage	200kg
Engine	Kubota Z 602-10.9W /3200rpm
Electric Motor	2.2kW/ 230V
Max Translation Speed	2.7km/h
Max Surmountable Slope	25%
Overall Weight	2660kg

