

# MBS ACCESS

01376 583 967

WWW.MBSACCESS.CO.UK

BLUELIFT SA22-11



Hybrid engine can be used on diesel or electric

160 degrees basket rotation

Compact, lightweight and easily transportable

Self-Stabilizing system

Translation intermittent sound alarm

Come home feature

Can be used on 110 or 240 volts

Driving double speed

Track width adjusted system

Electro-hydraulic transmission

A protection with pressure relief valve on the hydraulic system

Automatic opening of the brake when the rotation and translation begins

Radio Remote Control

Complete stabilisation warning light

Automatic start and stop

Emergency push-button with engine stop

Hand pump for the emergency descent of the platform

Locks for safety belts on the platform

Priority of platform controls



MEASUREMENTS	METRIC (M)
Working Height	21m
Horizontal Outreach	10.8m
Total Weight	3000kg
Max Translation Speed	1.5km/h
Load Capacity	200kg
Control Speed	0.4m/sec
Engine	HondaiGX440 15HP
Electric Voltage	12v
Oil Tank Capacity	40L
Maximum Gradient	28%
Max Wind Speed	12.5m/sec
Max Manual Force	40daN
Turret Rotation	340°
SET UP POISTIONS	
Min (Yellow)	1984mm x 5671mm
Med (Green)	2996mm x 5214mm
Max (Blue)	3975mm x 4634mm
WIDTH ADJUSTING TRACK SYSTEM	
Min Width	900mm
Max Width	1200mm

