

MBS ACCESS

01376 583 967

WWW.MBSACCESS.CO.UK

HINOWA 17.75



230kg Capacity for the whole working area

Set up within a 3m squared area

Speed and precision of the movement

Integrated guides for lifting with a forklift

Can be used internally thanks to the lithium battery (Lithium Only)

17m working height and 7.5m continuous outreach with flush with the wall trajectory

The new jib allows work in all conditions with two operators up to 230kgs of weight which increases the productivity as the operator is also able to carry tools

The remote control includes simple and comfortable controls such as self-stabilization, arm movement and translation

Auto2speed traction system allows the machine to reach an optimal translation speed of 3.6km/h, to move quickly from one place to another

A practical display on the controls provides the operator with important information

New parameters have been added to the system – the service icon informs the operator when the machine has to be serviced in the future

NOW AVAILABLE IN LITHIUM



MEASUREMENTS	METRIC (M)
Working Height	17.06m
Horizontal Outreach	7.50m
Machine Width	798/1086mm
Transport Length	4.52m
Transport Height	1.99m
Cage Dimensions	1335x690xh.1100mm
Total Weight	2230kg
Max Slope Allowance in Travel Mode	16°/28.7%
Max Travel Speed	1.8km/h
Thermic Engine Diesel	Honda iGX440-12.7CV 3600rpm
Electric Motor	2.2kw-230V-50Hz 1500rpm

